

## LESEN PENSIJILAN BARANGAN

*Product Certification Licence*



SIRIM

**SIRIM QAS International Sdn. Bhd.** dengan ini menganugerahkan kepada  
*SIRIM QAS International Sdn. Bhd. hereby grants to*

**SIRIJAYA INDUSTRIES SDN. BHD.**  
**NO. 9, LEBUH PERUSAHAAN KLEBANG 9**  
**IGB INTERNATIONAL INDUSTRIAL PARK**  
**31200 CHEMOR**  
**PERAK, MALAYSIA**

**Lesen untuk menggunakan Tanda Pensijilan di atas barangan**  
*a licence to use the Certification Mark on*

**CABLE TRAY**

**Please refer to detail in the SCHEDULE**

**sebagai mematuhi keperluan**  
*as complying with*

**MS IEC 61537 : 2007**



**Nur Fadhilah binti Muhammad**  
Ketua Pegawai Eksekutif  
*Chief Executive Officer*  
SIRIM QAS International Sdn. Bhd.



# SCHEDULE

**SIRIJAYA INDUSTRIES SDN. BHD.**



Trade Mark	: SJ TRUNK
Model	: Electro-Galvanized (EG) steel, Epoxy-powder coating; SCT/U-(50x13) EG, SCT/U-(75x13) EG, SCT/U-(100x13) EG, SCT/U-(150x13) EG, SCT/U-(200x17) EG, SCT/U-(250x17) EG, SCT/U-(300x17) EG, SCT/U-(350x20) EG, SCT/U-(400x20) EG, SCT/U-(450x20) EG, SCT/U-(500x25) EG, SCT/U-(550x25) EG, SCT/U-(600x25) EG, SCT/U-(650x25) EG, SCT/U-(700x25) EG, SCT/U-(750x25) EG, SCT/U-(800x25) EG, SCT/U-(850x25) EG, SCT/U-(900x25) EG, SCT/U-(950x25) EG, SCT/U-(1000x25) EG
Rating	: System component: Metallic, Non-flame propagating, With electrical continuity characteristics, Electrical conductivity, With metallic coating, Minimum temperature: 5°C, Maximum temperature: 40°C, Perforation in the base area: Class C, Impact resistance: 50J
Type	: Perforated.
Size	: Length, mm: 2438, Width x Height x Thickness, mm: 50 x 13 x 1.5 (SCT/U-(50x13) EG), 75 x 13 x 1.5 (SCT/U-(75x13) EG), 100 x 13 x 1.5 (SCT/U-(100x13) EG), 150 x 13 x 1.5 (SCT/U-(150x13) EG), 200 x 17 x 1.5 (SCT/U-(200x17) EG), 250 x 17 x 1.5 (SCT/U-(250x17) EG), 300 x 17 x 1.5 (SCT/U-(300x17) EG), 350 x 20 x 2.0 (SCT/U-(350x20) EG), 400 x 20 x 2.0 (SCT/U-(400x20) EG), 450 x 20 x 2.0 (SCT/U-(450x20) EG), 500 x 25 x 2.0 (SCT/U-(500x25) EG), 550 x 25 x 2.0 (SCT/U-(550x25) EG), 600 x 25 x 2.0 (SCT/U-(600x25) EG)
Perforated.	
Size	: Length, mm: 2438, Width x Height x Thickness, mm: 650 x 25 x 2.0 (SCT/U-(650x25) EG), 700 x 25 x 2.0 (SCT/U-(700x25) EG), 750 x 25 x 2.0 (SCT/U-(750x25) EG), 800 x 25 x 2.0 (SCT/U-(800x25) EG), 850 x 25 x 2.0 (SCT/U-(850x25) EG), 900 x 25 x 2.0 (SCT/U-(900x25) EG), 950 x 25 x 2.0 (SCT/U-(950x25) EG), 1000 x 25 x 2.0 (SCT/U-(1000x25) EG)

# SCHEDULE

**SIRIJAYA INDUSTRIES SDN. BHD.**



Trade Mark	: SJ TRUNK
Model	: Superdyma (SD) steel; SCT/U-(50x13) SD, SCT/U-(75x13) SD, SCT/U-(100x13) SD, SCT/U-(150x13) SD, SCT/U-(200x17) SD, SCT/U-(250x17) SD, SCT/U-(300x17) SD, SCT/U-(350x20) SD, SCT/U-(400x20) SD, SCT/U-(450x20) SD, SCT/U-(500x25) SD, SCT/U-(550x25) SD, SCT/U-(600x25) SD, SCT/U-(650x25) SD, SCT/U-(700x25) SD, SCT/U-(750x25) SD, SCT/U-(800x25) SD, SCT/U-(850x25) SD, SCT/U-(900x25) SD, SCT/U-(950x25) SD, SCT/U-(1000x25) SD
Rating	: System component: Metallic, Non-flame propagating, With electrical continuity characteristics, Electrical conductivity, With metallic coating, Minimum temperature: 5°C, Maximum temperature: 40°C, Perforation in the base area: Class C, Impact resistance: 50J
Type	: Perforated
Size	: Length, mm: 2438, Width x Height x Thickness, mm: 50 x 13 x 1.5 (SCT/U-(50x13) SD), 75 x 13 x 1.5 (SCT/U-(75x13) SD), 100 x 13 x 1.5 (SCT/U-(100x13) SD), 150 x 13 x 1.5 (SCT/U-(150x13) SD), 200 x 17 x 1.5 (SCT/U-(200x17) SD), 250 x 17 x 1.5 (SCT/U-(250x17) SD), 300 x 17 x 1.5 (SCT/U-(300x17) SD), 350 x 20 x 2.0 (SCT/U-(350x20) SD), 400 x 20 x 2.0 (SCT/U-(400x20) SD), 450 x 20 x 2.0 (SCT/U-(450x20) SD), 500 x 25 x 2.0 (SCT/U-(500x25) SD), 550 x 25 x 2.0 (SCT/U-(550x25) SD), 600 x 25 x 2.0 (SCT/U-(600x25) SD)
Perforated	
Size	: Length, mm: 2438, Width x Height x Thickness, mm: 650 x 25 x 2.0 (SCT/U-(650x25) SD), 700 x 25 x 2.0 (SCT/U-(700x25) SD), 750 x 25 x 2.0 (SCT/U-(750x25) SD), 800 x 25 x 2.0 (SCT/U-(800x25) SD), 850 x 25 x 2.0 (SCT/U-(850x25) SD), 900 x 25 x 2.0 (SCT/U-(900x25) SD), 950 x 25 x 2.0 (SCT/U-(950x25) SD), 1000 x 25 x 2.0 (SCT/U-(1000x25) SD)

# SCHEDULE

**SIRIJAYA INDUSTRIES SDN. BHD.**



Trade Mark	: SJ TRUNK
Model	: Galvanized Iron (GI) steel; SCT/U-(50x13) GI, SCT/U-(75x13) GI, SCT/U-(100x13) GI, SCT/U-(150x13) GI, SCT/U-(200x17) GI, SCT/U-(250x17) GI, SCT/U-(300x17) GI, SCT/U-(350x20) GI, SCT/U-(400x20) GI, SCT/U-(450x20) GI, SCT/U-(500x25) GI, SCT/U-(550x25) GI, SCT/U-(600x25) GI, SCT/U-(650x25) GI, SCT/U-(700x25) GI, SCT/U-(750x25) GI, SCT/U-(800x25) GI, SCT/U-(850x25) GI, SCT/U-(900x25) GI, SCT/U-(950x25) GI, SCT/U-(1000x25) GI
Rating	: System component: Metallic, Non-flame propagating, With electrical continuity characteristics, Electrical conductivity, With metallic coating, Minimum temperature: 5°C, Maximum temperature: 40°C, Perforation in the base area: Class C, Impact resistance: 50J
Type	: Perforated
Size	: Length, mm: 2438, Width x Height x Thickness, mm: 50 x 13 x 1.5 (SCT/U-(50x13) GI), 75 x 13 x 1.5 (SCT/U-(75x13) GI), 100 x 13 x 1.5 (SCT/U-(100x13) GI), 150 x 13 x 1.5 (SCT/U-(150x13) GI), 200 x 17 x 1.5 (SCT/U-(200x17) GI), 250 x 17 x 1.5 (SCT/U-(250x17) GI), 300 x 17 x 1.5 (SCT/U-(300x17) GI), 350 x 20 x 2.0 (SCT/U-(350x20) GI), 400 x 20 x 2.0 (SCT/U-(400x20) GI), 450 x 20 x 2.0 (SCT/U-(450x20) GI), 500 x 25 x 2.0 (SCT/U-(500x25) GI), 550 x 25 x 2.0 (SCT/U-(550x25) GI), 600 x 25 x 2.0 (SCT/U-(600x25) GI)
Perforated	
Size	: Length, mm: 2438, Width x Height x Thickness, mm: 650 x 25 x 2.0 (SCT/U-(650x25) GI), 700 x 25 x 2.0 (SCT/U-(700x25) GI), 750 x 25 x 2.0 (SCT/U-(750x25) GI), 800 x 25 x 2.0 (SCT/U-(800x25) GI), 850 x 25 x 2.0 (SCT/U-(850x25) GI), 900 x 25 x 2.0 (SCT/U-(900x25) GI), 950 x 25 x 2.0 (SCT/U-(950x25) GI), 1000 x 25 x 2.0 (SCT/U-(1000x25) GI)

TEST REPORT NO. : 2018MA1132, 2020MA1086, 2021MA0363

**End of page**