

LESEN PENSIJILAN BARANGAN

Product Certification Licence



**SIRIM QAS International Sdn. Bhd. dengan ini menganugerahkan kepada
SIRIM QAS International Sdn. Bhd. hereby grants to**

**SIRIJAYA INDUSTRIES SDN. BHD.
NO. 9, LEBUH PERUSAHAAN KLEBANG 9
IGB INTERNATIONAL INDUSTRIAL PARK
31200 CHEMOR
PERAK, MALAYSIA**

**Lesen untuk menggunakan Tanda Pensijilan di atas barangan
a licence to use the Certification Mark on**

CABLE TRUNKING AND DUCTING SYSTEMS FOR ELECTRICAL INSTALLATIONS

Please refer to detail in the SCHEDULE

**sebagai mematuhi keperluan
as complying with**

MS IEC 61084-1 : 2006



Nur Fadhilah binti Muhammad
Ketua Pegawai Eksekutif
Chief Executive Officer
SIRIM QAS International Sdn. Bhd.



SCHEDULE

SIRIJAYA INDUSTRIES SDN. BHD.



Trade Mark : SJ TRUNK
Model : Electro-galvanised (EG) steel, Epoxy powder-coated; STK 1/2, STK 2/2, STK 2/3, STK 2/4, STK 3/3, STK 3/4, STK 3/6, STK 4/4, STK 4/6, STK 4/8, STK 2/6, STK 6/6, STK 2/8, STK 3/8, STK 6/8, STK 2/10, STK 3/10, STK 4/10.
Rating : Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.
Type : Straight cable trunking (with cover)
Size : Length, mm: 2438, Width x Height x Thickness, mm: 50 x 25 x 1.0 (STK 1/2), 50 x 50 x 1.0 (STK 2/2), 75 x 50 x 1.2 (STK 2/3), 100 x 50 x 1.2 (STK 2/4), 75 x 75 x 1.2 (STK 3/3), 100 x 75 x 1.2 (STK 3/4), 150 x 75 x 1.4 (STK 3/6), 100 x 100 x 1.4 (STK 4/4), 150 x 100 x 1.4 (STK 4/6), 200 x 100 x 1.6 (STK 4/8), 150 x 50 x 1.6 (STK 2/6), 150 x 150 x 1.6 (STK 6/6), 200 x 50 x 1.6 (STK 2/8), 200 x 75 x 1.6 (STK 3/8), 200 x 150 x 1.6 (STK 6/8), 250 x 50 x 1.6 (STK 2/10), 250 x 75 x 1.6 (STK 3/10), 250 x 150 x 1.6 (STK 4/10).

Straight cable trunking (with cover)

Trade Mark : SJ TRUNK
Model : Electro-galvanised (EG) steel, Epoxy powder-coated; STK 2/12, STK 3/12, STK 4/12, STK 2/14
Rating : Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.
Type : Straight cable trunking (with cover)
Size : Length, mm: 2438, Width x Height x Thickness, mm: 300 x 50 x 1.6 (STK 2/12), 300 x 75 x 1.6 (STK 3/12), 300 x 100 x 1.6 (STK 4/12), 350 x 50 x 1.6 (STK 2/14).

Straight cable trunking (with cover)

SCHEDULE

SIRIJAYA INDUSTRIES SDN. BHD.



Trade Mark : SJ TRUNK
Model : Superdyma; STK 1/2 SD, STK 2/2 SD, STK 2/3 SD, STK 3/3 SD, STK 2/4 SD, STK 3/4 SD, STK 4/4 SD, STK 2/6 SD, STK 3/6 SD, STK 4/6 SD, STK 6/6 SD, STK 2/8 SD, STK 3/8 SD, STK 4/8 SD, STK 6/8 SD, STK 2/10 SD, STK 3/10 SD, STK 4/10 SD.
Rating : Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.
Type : Straight cable trunking (with cover)
Size : Length, mm: 2438, Width x Height x Thickness, mm: 50 x 25 x 1.0 (STK 1/2 SD), 50 x 50 x 1.0 (STK 2/2 SD), 75 x 50 x 1.2 (STK 2/3 SD), 75 x 75 x 1.2 (STK 3/3 SD), 100 x 50 x 1.2 (STK 2/4 SD), 100 x 75 x 1.2 (STK 3/4 SD), 100 x 100 x 1.5 (STK 4/4 SD), 100 x 50 x 1.5 (STK 2/6 SD), 150 x 75 x 1.5 (STK 3/6 SD), 150 x 100 x 1.5 (STK 4/6 SD), 150 x 50 x 1.5 (STK 6/6 SD), 200 x 50 x 1.6 (STK 2/8 SD), 200 x 75 x 1.6 (STK 3/8 SD), 200 x 100 x 1.6 (STK 4/8 SD), 200 x 150 x 1.6 (STK 6/8 SD), 250 x 50 x 1.6 (STK 2/10 SD), 250 x 75 x 1.6 (STK 3/10 SD), 250 x 150 x 1.6 (STK 4/10 SD).

Straight cable trunking (with cover)

Trade Mark : SJ TRUNK
Model : Superdyma; STK 2/12 SD, STK 3/12 SD, STK 4/12 SD, STK 2/14 SD.
Rating : Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.
Type : Straight cable trunking (with cover)
Size : Length, mm: 2438, Width x Height x Thickness, mm: 300 x 50 x 1.6 (STK 2/12 SD), 300 x 75 x 1.6 (STK 3/12 SD), 300 x 100 x 1.6 (STK 4/12 SD), 350 x 50 x 1.6 (STK 2/14 SD).

Straight cable trunking (with cover)

SCHEDULE

SIRIJAYA INDUSTRIES SDN. BHD.



Trade Mark : SJ TRUNK
Model : Galvanized Iron (GI) steel; STK 1/2 GI, STK 2/2 GI, STK 2/3 GI, STK 3/3 GI, STK 2/4 GI, STK 3/4 GI, STK 4/4 GI, STK 2/6 GI, STK 3/6 GI, STK 4/6 GI, STK 6/6 GI, STK 2/8 GI, STK 3/8 GI, STK 4/8 GI, STK 6/8 GI, STK 2/10 GI, STK 3/10 GI, STK 4/10 GI.
Rating : Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.
Type : Straight cable trunking (with cover).
Size : Length, mm: 2438, Width x Height x Thickness, mm: 50 x 25 x 1.0 (STK 1/2 GI), 50 x 50 x 1.0 (STK 2/2 GI), 75 x 50 x 1.2 (STK 2/3 GI), 75 x 75 x 1.2 (STK 3/3 GI), 100 x 50 x 1.2 (STK 2/4 GI), 100 x 75 x 1.2 (STK 3/4 GI), 100 x 100 x 1.2 (STK 4/4 GI), 150 x 50 x 1.6 (STK 2/6 GI), 150 x 75 x 1.6 (STK 3/6 GI), 150 x 100 x 1.6 (STK 4/6 GI), 150 x 150 x 1.6 (STK 6/6 GI), 200 x 50 x 1.6 (STK 2/8 GI), 200 x 75 x 1.6 (STK 3/8 GI), 200 x 100 x 1.6 (STK 4/8 GI), 200 x 150 x 1.6 (STK 6/8 GI), 250 x 50 x 1.6 (STK 2/10 GI), 250 x 75 x 1.6 (STK 3/10 GI), 250 x 100 x 1.6 (STK 4/10 GI).

Trade Mark : SJ TRUNK
Model : Galvanized Iron (GI) steel; STK 2/12 GI, STK 3/12 GI, STK 4/12 GI, STK 2/14 GI.
Rating : Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.
Type : Straight cable trunking (with cover)
Size : Length, mm: 2438, Width x Height x Thickness, mm: 300 x 50 x 1.6 (STK 2/12 GI), 300 x 75 x 1.6 (STK 3/12 GI), 300 x 100 x 1.6 (STK 4/12 GI), 350 x 50 x 1.6 (STK 2/14 GI).

TEST REPORT NO. : 2016EEA0141, 2019EA0167, 2019EA0769, 2021EA0352

End of page