

# LESEN PENSIJILAN BARANGAN

## *Product Certification Licence*



SIRIM

**SIRIM QAS International Sdn. Bhd. dengan ini menganugerahkan kepada**  
*SIRIM QAS International Sdn. Bhd. hereby grants to*

**SIRIJAYA INDUSTRIES SDN. BHD.  
NO. 9, LEBUH PERUSAHAAN KLEBANG 9  
IGB INTERNATIONAL INDUSTRIAL PARK  
31200 CHEMOR  
PERAK, MALAYSIA**

**Lesen untuk menggunakan Tanda Pensijilan di atas barangan**  
*a licence to use the Certification Mark on*

**CABLE TRUNKING AND DUCTING SYSTEMS FOR ELECTRICAL INSTALLATIONS**

**Please refer to detail in the SCHEDULE**

**sebagai mematuhi keperluan**  
*as complying with*

**MS IEC 61084-1 : 2006**



**Ts. Md. Adha bin Katni @ Rahmat**  
Ketua Pegawai Eksekutif  
*Chief Executive Officer*  
SIRIM QAS International Sdn. Bhd.



# SCHEDULE

**SIRIJAYA INDUSTRIES SDN. BHD.**



Trade Mark : SJ TRUNK  
Model : Electro-galvanised (EG) steel, Epoxy powder-coated; STK 1/2, STK 2/2, STK 2/3, STK 2/4, STK 3/3, STK 3/4, STK 3/6, STK 4/4, STK 4/6, STK 4/8, STK 2/6, STK 6/6, STK 2/8, STK 3/8, STK 6/8, STK 2/10, STK 3/10, STK 4/10.  
Rating : Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.  
Type : Straight cable trunking (with cover)  
Size : Length, mm: 2438, Width x Height x Thickness, mm: 50 x 25 x 1.0 (STK 1/2), 50 x 50 x 1.0 (STK 2/2), 75 x 50 x 1.2 (STK 2/3), 100 x 50 x 1.2 (STK 2/4), 75 x 75 x 1.2 (STK 3/3), 100 x 75 x 1.2 (STK 3/4), 150 x 75 x 1.6 (STK 3/6), 100 x 100 x 1.2 (STK 4/4), 150 x 100 x 1.6 (STK 4/6), 200 x 100 x 1.6 (STK 4/8), 150 x 50 x 1.6 (STK 2/6), 150 x 150 x 1.6 (STK 6/6), 200 x 50 x 1.6 (STK 2/8), 200 x 75 x 1.6 (STK 3/8), 200 x 150 x 1.6 (STK 6/8), 250 x 50 x 1.6 (STK 2/10), 250 x 75 x 1.6 (STK 3/10), 250 x 100 x 1.6 (STK 4/10).

Straight cable trunking (with cover)

Trade Mark : SJ TRUNK  
Model : Electro-galvanised (EG) steel, Epoxy powder-coated; STK 2/12, STK 3/12, STK 4/12, STK 2/14  
Rating : Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.  
Type : Straight cable trunking (with cover)  
Size : Length, mm: 2438, Width x Height x Thickness, mm: 300 x 50 x 1.6 (STK 2/12), 300 x 75 x 1.6 (STK 3/12), 300 x 100 x 1.6 (STK 4/12), 350 x 50 x 1.6 (STK 2/14).

Straight cable trunking (with cover)

# SCHEDULE

**SIRIJAYA INDUSTRIES SDN. BHD.**



Trade Mark : SJ TRUNK  
 Model : Superdyma; STK 1/2 SD, STK 2/2 SD, STK 2/3 SD, STK 3/3 SD, STK 2/4 SD, STK 3/4 SD, STK 4/4 SD, STK 2/6 SD, STK 3/6 SD, STK 4/6 SD, STK 6/6 SD, STK 2/8 SD, STK 3/8 SD, STK 4/8 SD, STK 6/8 SD, STK 2/10 SD, STK 3/10 SD, STK 4/10 SD.  
 Rating : Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.  
 Type : Straight cable trunking (with cover)  
 Size : Length, mm: 2438, Width x Height x Thickness, mm: 50 x 25 x 1.0 (STK 1/2 SD), 50 x 50 x 1.0 (STK 2/2 SD), 75 x 50 x 1.2 (STK 2/3 SD), 75 x 75 x 1.2 (STK 3/3 SD), 100 x 50 x 1.2 (STK 2/4 SD), 100 x 75 x 1.2 (STK 3/4 SD), 100 x 100 x 1.2 (STK 4/4 SD), 150 x 50 x 1.6 (STK 2/6 SD), 150 x 75 x 1.6 (STK 3/6 SD), 150 x 100 x 1.6 (STK 4/6 SD), 150 x 150 x 1.6 (STK 6/6 SD), 200 x 50 x 1.6 (STK 2/8 SD), 200 x 75 x 1.6 (STK 3/8 SD), 200 x 100 x 1.6 (STK 4/8 SD), 200 x 150 x 1.6 (STK 6/8 SD), 250 x 50 x 1.6 (STK 2/10 SD), 250 x 75 x 1.6 (STK 3/10 SD), 250 x 100 x 1.6 (STK 4/10 SD).

Straight cable trunking (with cover)

Trade Mark : SJ TRUNK  
 Model : Superdyma; STK 2/12 SD, STK 3/12 SD, STK 4/12 SD, STK 2/14 SD.  
 Rating : Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.  
 Type : Straight cable trunking (with cover)  
 Size : Length, mm: 2438, Width x Height x Thickness, mm: 300 x 50 x 1.6 (STK 2/12 SD), 300 x 75 x 1.6 (STK 3/12 SD), 300 x 100 x 1.6 (STK 4/12 SD), 350 x 50 x 1.6 (STK 2/14 SD).

Straight cable trunking (with cover)

Trade Mark : SJ TRUNK  
 Model : Galvanized Iron (GI) steel; STK 1/2 GI, STK 2/2 GI, STK 2/3 GI, STK 3/3 GI, STK 2/4 GI, STK 3/4 GI, STK 4/4 GI, STK 2/6 GI, STK 3/6 GI, STK 4/6 GI, STK 6/6 GI, STK 2/8 GI, STK 3/8 GI, STK 4/8 GI, STK 6/8 GI, STK 2/10 GI, STK 3/10 GI, STK 4/10 GI.  
 Rating : Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.  
 Type : Straight cable trunking (with cover).  
 Size : Length, mm: 2438, Width x Height x Thickness, mm: 50 x 25 x 1.0 (STK 1/2 GI), 50 x 50 x 1.0 (STK 2/2 GI), 75 x 50 x 1.2 (STK 2/3 GI), 75 x 75 x 1.2 (STK 3/3 GI), 100 x 50 x 1.2 (STK 2/4 GI), 100 x 75 x 1.2 (STK 3/4 GI), 100 x 100 x 1.2 (STK 4/4 GI), 150 x 50 x 1.6 (STK 2/6 GI), 150 x 75 x 1.6 (STK 3/6 GI), 150 x 100 x 1.6 (STK 4/6 GI), 150 x 150 x 1.6 (STK 6/6 GI), 200 x 50 x 1.6 (STK 2/8 GI), 200 x 75 x 1.6 (STK 3/8 GI), 200 x 100 x 1.6 (STK 4/8 GI), 200 x 150 x 1.6 (STK 6/8 GI), 250 x 50 x 1.6 (STK 2/10 GI), 250 x 75 x 1.6 (STK 3/10 GI), 250 x 100 x 1.6 (STK 4/10 GI).

# SCHEDULE

## SIRIJAYA INDUSTRIES SDN. BHD.



Trade Mark	: SJ TRUNK
Model	: Galvanized Iron (GI) steel; STK 2/12 GI, STK 3/12 GI, STK 4/12 GI, STK 2/14 GI.
Rating	: Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.
Type	: Straight cable trunking (with cover)
Size	: Length, mm: 2438, Width x Height x Thickness, mm: 300 x 50 x 1.6 (STK 2/12 GI), 300 x 75 x 1.6 (STK 3/12 GI), 300 x 100 x 1.6 (STK 4/12 GI), 350 x 50 x 1.6 (STK 2/14 GI).
Trade Mark	: SJ TRUNK
Model	: Galvanized Hot Dip Zinc Alloyed with Aluminium and Magnesium steel; STK 1/2 PM, STK 2/2 PM, STK 2/3 PM, STK 3/3 PM, STK 2/4 PM, STK 3/4 PM, STK 4/4 PM, STK 2/6 PM, STK 3/6 PM, STK 4/6 PM, STK 6/6 PM, STK 2/8 PM, STK 3/8 PM, STK 4/8 PM, STK 6/8 PM, STK 2/10 PM, STK 3/10 PM, STK 4/10 PM, STK 2/12 PM, STK 3/12 PM, STK 4/12 PM, STK 2/14 PM.
Rating	: Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.
Type	: Straight cable trunking (with cover).
Size	: Length, mm: 2438, Width x Height x Thickness, mm: 50 x 25 x 1.0 (STK 1/2 PM), 50 x 50 x 1.0 (STK 2/2 PM), 75 x 50 x 1.2 (STK 2/3 PM), 75 x 75 x 1.2 (STK 3/3 PM), 100 x 50 x 1.2 (STK 2/4 PM), 100 x 75 x 1.2 (STK 3/4 PM), 100 x 100 x 1.2 (STK 4/4 PM), 150 x 50 x 1.6 (STK 2/6 PM), 150 x 75 x 1.6 (STK 3/6 PM), 150 x 100 x 1.6 (STK 4/6 PM), 150 x 150 x 1.6 (STK 6/6 PM), 200 x 50 x 1.6 (STK 2/8 PM), 200 x 75 x 1.6 (STK 3/8 PM), 200 x 100 x 1.6 (STK 4/8 PM), 200 x 150 x 1.6 (STK 6/8 PM), 250 x 50 x 1.6 (STK 2/10 PM), 250 x 75 x 1.6 (STK 3/10 PM), 250 x 100 x 1.6 (STK 4/10 PM), 300 x 50 x 1.6 (STK 2/12 PM), 300 x 75 x 1.6 (STK 3/12 PM), 300 x 100 x 1.6 (STK 4/12 PM), 350 x 50 x 1.6 (STK 2/14 PM).

TEST REPORT NO. : 2019EA0769, 2021EA0352, 2024EA0523, 2024EA1558,  
2023EA0758-A2

**End of page**