



No Lesen : PC002263

Licence No :

LESEN PENSIJILAN BARANGAN

Product Certification Licence



SIRIM Berhad dengan ini menganugerahkan kepada
SIRIM Berhad hereby grants to

SIRIJAYA INDUSTRIES SDN. BHD.
NO. 9, LEBUH PERUSAHAAN KLEBANG 9
IGB INTERNATIONAL INDUSTRIAL PARK
31200 CHEMOR
PERAK, MALAYSIA

Lesen untuk menggunakan Tanda Pensijilan di atas barangan
a licence to use the Certification Mark on

CABLE TRUNKING AND DUCTING SYSTEMS FOR ELECTRICAL INSTALLATIONS

Please refer to detail in the SCHEDULE

sebagai mematuhi keperluan
as complying with

MS IEC 61084-1 : 2006

FAUZIAH BINTI FADZIL

Pemangku Ketua Pegawai Penilaian Pematuhan
Covering Chief Conformity Assessment Officer
Bahagian Penilaian Pematuhan
Conformity Assessment Division
SIRIM Berhad



SIRIM Berhad
((No. Syarikat 199501038272(367474-V)))

1, Persiaran Dato' Menteri
P.O. Box 7035, Seksyen 2
40700 Shah Alam
Selangor
MALAYSIA.

Tel : 603-5544 6000
Emel : web@sirim.my

Tarikh Mula Pensijilan : 15 April 2016

Certified Since

Sah Sehingga : 15 April 2027

Valid Until

Tarikh Dikeluarkan : 04 August 2026

Issue Date

No Siri : 131280

Serial No

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM Berhad
This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM Berhad



No Lesen : PC002263

Licence No :

SCHEDULE

SIRIJAYA INDUSTRIES SDN. BHD.



Trade Mark : SJ TRUNK
Model : Electro-galvanised (EG) steel, Epoxy powder-coated; STK 1/2, STK 2/2, STK 2/3, STK 2/4, STK 3/3, STK 3/4, STK 3/6, STK 4/4, STK 4/6, STK 4/8, STK 2/6, STK 6/6, STK 2/8, STK 3/8, STK 6/8, STK 2/10, STK 3/10, STK 4/10.
Rating : Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.
Type : Straight cable trunking (with cover)
Size : Length, mm: 2438, Width x Height x Thickness, mm: 50 x 25 x 1.0 (STK 1/2), 50 x 50 x 1.0 (STK 2/2), 75 x 50 x 1.2 (STK 2/3), 100 x 50 x 1.2 (STK 2/4), 75 x 75 x 1.2 (STK 3/3), 100 x 75 x 1.2 (STK 3/4), 150 x 75 x 1.6 (STK 3/6), 100 x 100 x 1.2 (STK 4/4), 150 x 100 x 1.6 (STK 4/6), 200 x 100 x 1.6 (STK 4/8), 150 x 50 x 1.6 (STK 2/6), 150 x 150 x 1.6 (STK 6/6), 200 x 50 x 1.6 (STK 2/8), 200 x 75 x 1.6 (STK 3/8), 200 x 150 x 1.6 (STK 6/8), 250 x 50 x 1.6 (STK 2/10), 250 x 75 x 1.6 (STK 3/10), 250 x 100 x 1.6 (STK 4/10).

Straight cable trunking (with cover)

Trade Mark : SJ TRUNK
Model : Electro-galvanised (EG) steel, Epoxy powder-coated; STK 2/12, STK 3/12, STK 4/12, STK 2/14
Rating : Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.
Type : Straight cable trunking (with cover)
Size : Length, mm: 2438, Width x Height x Thickness, mm: 300 x 50 x 1.6 (STK 2/12), 300 x 75 x 1.6 (STK 3/12), 300 x 100 x 1.6 (STK 4/12), 350 x 50 x 1.6 (STK 2/14).

Straight cable trunking (with cover)

SIRIM Berhad
((No. Syarikat 199501038272(367474-V)))

1, Persiaran Dato' Menteri
P.O. Box 7035, Seksyen 2
40700 Shah Alam
Selangor
MALAYSIA.

Tel : 603-5544 6000
Emel : web@sirim.my

www.sirim.my
<https://www.malysiancertified.com.my>

Tarikh Mula Pensijilan : 15 April 2016

Certified Since

Sah Sehingga : 15 April 2027

Valid Until

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM Berhad
This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM Berhad

Tarikh Dikeluarkan : 04 August 2026

Issue Date

No Siri : 131280

Serial No



No Lesen : **PC002263**

Licence No :

SCHEDULE

SIRIJAYA INDUSTRIES SDN. BHD.



Trade Mark : SJ TRUNK
Model : Superdyma; STK 1/2 SD, STK 2/2 SD, STK 2/3 SD, STK 3/3 SD, STK 2/4 SD, STK 3/4 SD, STK 4/4 SD, STK 2/6 SD, STK 3/6 SD, STK 4/6 SD, STK 6/6 SD, STK 2/8 SD, STK 3/8 SD, STK 4/8 SD, STK 6/8 SD, STK 2/10 SD, STK 3/10 SD, STK 4/10 SD.
Rating : Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.
Type : Straight cable trunking (with cover)
Size : Length, mm: 2438, Width x Height x Thickness, mm: 50 x 25 x 1.0 (STK 1/2 SD), 50 x 50 x 1.0 (STK 2/2 SD), 75 x 50 x 1.2 (STK 2/3 SD), 75 x 75 x 1.2 (STK 3/3 SD), 100 x 50 x 1.2 (STK 2/4 SD), 100 x 75 x 1.2 (STK 3/4 SD), 100 x 100 x 1.2 (STK 4/4 SD), 150 x 50 x 1.6 (STK 2/6 SD), 150 x 75 x 1.6 (STK 3/6 SD), 150 x 100 x 1.6 (STK 4/6 SD), 150 x 150 x 1.6 (STK 6/6 SD), 200 x 50 x 1.6 (STK 2/8 SD), 200 x 75 x 1.6 (STK 3/8 SD), 200 x 100 x 1.6 (STK 4/8 SD), 200 x 150 x 1.6 (STK 6/8 SD), 250 x 50 x 1.6 (STK 2/10 SD), 250 x 75 x 1.6 (STK 3/10 SD), 250 x 100 x 1.6 (STK 4/10 SD).

Straight cable trunking (with cover)

Trade Mark : SJ TRUNK
Model : Superdyma; STK 2/12 SD, STK 3/12 SD, STK 4/12 SD, STK 2/14 SD.
Rating : Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.
Type : Straight cable trunking (with cover)
Size : Length, mm: 2438, Width x Height x Thickness, mm: 300 x 50 x 1.6 (STK 2/12 SD), 300 x 75 x 1.6 (STK 3/12 SD), 300 x 100 x 1.6 (STK 4/12 SD), 350 x 50 x 1.6 (STK 2/14 SD).

Straight cable trunking (with cover)

Trade Mark : SJ TRUNK
Model : Galvanized Iron (GI) steel; STK 1/2 GI, STK 2/2 GI, STK 2/3 GI, STK 3/3 GI, STK 2/4 GI, STK 3/4 GI, STK 4/4 GI, STK 2/6 GI, STK 3/6 GI, STK 4/6 GI, STK 6/6 GI, STK 2/8 GI, STK 3/8 GI, STK 4/8 GI, STK 6/8 GI, STK 2/10 GI, STK 3/10 GI, STK 4/10 GI.
Rating : Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.
Type : Straight cable trunking (with cover).
Size : Length, mm: 2438, Width x Height x Thickness, mm: 50 x 25 x 1.0 (STK 1/2 GI), 50 x 50 x 1.0 (STK 2/2 GI), 75 x 50 x 1.2 (STK 2/3 GI), 75 x 75 x 1.2 (STK 3/3 GI), 100 x 50 x 1.2 (STK 2/4 GI), 100 x 75 x 1.2 (STK 3/4 GI), 100 x 100 x 1.2 (STK 4/4 GI), 150 x 50 x 1.6 (STK 2/6 GI), 150 x 75 x 1.6 (STK 3/6 GI), 150 x 100 x 1.6 (STK 4/6 GI), 150 x 150 x 1.6 (STK 6/6 GI), 200 x 50 x 1.6 (STK 2/8 GI), 200 x 75 x 1.6 (STK 3/8 GI), 200 x 100 x 1.6 (STK 4/8 GI), 200 x 150 x 1.6 (STK 6/8 GI), 250 x 50 x 1.6 (STK 2/10 GI), 250 x 75 x 1.6 (STK 3/10 GI), 250 x 100 x 1.6 (STK 4/10 GI).

SIRIM Berhad
((No. Syarikat 199501038272(367474-V)))

1, Persiaran Dato' Menteri
P.O. Box 7035, Seksyen 2
40700 Shah Alam
Selangor
MALAYSIA.

Tel : 603-5544 6000
Emel : web@sirim.my

Tarikh Mula Pensijilan : 15 April 2016

Certified Since

Sah Sehingga : 15 April 2027

Valid Until

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM Berhad
This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM Berhad

Tarikh Dikeluarkan : 04 August 2026

Issue Date

No Siri : 131280

Serial No



No Lesen : PC002263

Licence No :

SCHEDULE

SIRIJAYA INDUSTRIES SDN. BHD.



Trade Mark	: SJ TRUNK
Model	: Galvanized Iron (GI) steel; STK 2/12 GI, STK 3/12 GI, STK 4/12 GI, STK 2/14 GI.
Rating	: Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.
Type	: Straight cable trunking (with cover)
Size	: Length, mm: 2438, Width x Height x Thickness, mm: 300 x 50 x 1.6 (STK 2/12 GI), 300 x 75 x 1.6 (STK 3/12 GI), 300 x 100 x 1.6 (STK 4/12 GI), 350 x 50 x 1.6 (STK 2/14 GI).
Trade Mark	: SJ TRUNK
Model	: Galvanized Hot Dip Zinc Alloyed with Aluminium and Magnesium steel; STK 1/2 PM, STK 2/2 PM, STK 2/3 PM, STK 3/3 PM, STK 2/4 PM, STK 3/4 PM, STK 4/4 PM, STK 2/6 PM, STK 3/6 PM, STK 4/6 PM, STK 6/6 PM, STK 2/8 PM, STK 3/8 PM, STK 4/8 PM, STK 6/8 PM, STK 2/10 PM, STK 3/10 PM, STK 4/10 PM, STK 2/12 PM, STK 3/12 PM, STK 4/12 PM, STK 2/14 PM.
Rating	: Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.
Type	: Straight cable trunking (with cover).
Size	: Length, mm: 2438, Width x Height x Thickness, mm: 50 x 25 x 1.0 (STK 1/2 PM), 50 x 50 x 1.0 (STK 2/2 PM), 75 x 50 x 1.2 (STK 2/3 PM), 75 x 75 x 1.2 (STK 3/3 PM), 100 x 50 x 1.2 (STK 2/4 PM), 100 x 75 x 1.2 (STK 3/4 PM), 100 x 100 x 1.2 (STK 4/4 PM), 150 x 50 x 1.6 (STK 2/6 PM), 150 x 75 x 1.6 (STK 3/6 PM), 150 x 100 x 1.6 (STK 4/6 PM), 150 x 150 x 1.6 (STK 6/6 PM), 200 x 50 x 1.6 (STK 2/8 PM), 200 x 75 x 1.6 (STK 3/8 PM), 200 x 100 x 1.6 (STK 4/8 PM), 200 x 150 x 1.6 (STK 6/8 PM), 250 x 50 x 1.6 (STK 2/10 PM), 250 x 75 x 1.6 (STK 3/10 PM), 250 x 100 x 1.6 (STK 4/10 PM), 300 x 50 x 1.6 (STK 2/12 PM), 300 x 75 x 1.6 (STK 3/12 PM), 300 x 100 x 1.6 (STK 4/12 PM), 350 x 50 x 1.6 (STK 2/14 PM).

SIRIM Berhad
((No. Syarikat 199501038272(367474-V)))

1, Persiaran Dato' Menteri
P.O. Box 7035, Seksyen 2
40700 Shah Alam
Selangor
MALAYSIA.

Tel : 603-5544 6000
Emel : web@sirim.my

www.sirim.my
<https://www.malysiancertified.com.my>

Tarikh Mula Pensijilan : 15 April 2016

Certified Since

Sah Sehingga : 15 April 2027

Valid Until

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM Berhad
This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM Berhad

Tarikh Dikeluarkan : 04 August 2026

Issue Date

No Siri : 131280

Serial No



No Lesen : PC002263

Licence No :

SCHEDULE

SIRIJAYA INDUSTRIES SDN. BHD.



Trade Mark : SJ TRUNK
Model : Cold rolled steel with Hot dipped galvanized; STK 1/2 HDG, STK 2/2 HDG, STK 2/3 HDG, STK 3/3 HDG, STK 2/4 HDG, STK 3/4 HDG, STK 4/4 HDG, STK 2/6 HDG, STK 3/6 HDG, STK 4/6 HDG, STK 6/6 HDG, STK 2/8 HDG, STK 3/8 HDG, STK 4/8 HDG, STK 6/8 HDG, STK 2/10 HDG, STK 3/10 HDG, STK 4/10 HDG, STK 6/10 HDG, STK 2/12 HDG, STK 3/12 HDG, STK 4/12 HDG, STK 6/12 HDG.
Rating : Classification: Metal trunking, Heavy mechanical stresses, Non-flame propagating, With electrical continuity characteristics.
Type : Straight cable trunking (with cover).
Size : Length, mm: 2438, Width x Height x Thickness, mm: 50 x 25 x 1.0 (STK 1/2 HDG), 50 x 50 x 1.0 (STK 2/2 HDG), 75 x 50 x 1.2 (STK 2/3 HDG), 75 x 75 x 1.2 (STK 3/3 HDG), 100 x 50 x 1.2 (STK 2/4 HDG), 100 x 75 x 1.2 (STK 3/4 HDG), 100 x 100 x 1.2 (STK 4/4 HDG), 150 x 50 x 1.6 (STK 2/6 HDG), 150 x 75 x 1.6 (STK 3/6 HDG), 150 x 100 x 1.6 (STK 4/6 HDG), 150 x 150 x 1.6 (STK 6/6 HDG), 200 x 50 x 1.6 (STK 2/8 HDG), 200 x 75 x 1.6 (STK 3/8 HDG), 200 x 100 x 1.6 (STK 4/8 HDG), 200 x 150 x 1.6 (STK 6/8 HDG), 250 x 50 x 1.6 (STK 2/10 HDG), 250 x 75 x 1.6 (STK 3/10 HDG), 250 x 100 x 1.6 (STK 4/10 HDG), 250 x 150 x 1.6 (STK 6/10 HDG), 300 x 50 x 1.6 (STK 2/12 HDG), 300 x 75 x 1.6 (STK 3/12 HDG), 300 x 100 x 1.6 (STK 4/12 HDG), 300 x 150 x 1.6 (STK 6/12 HDG).

Test report: 2026EA0391

TEST REPORT NO. : 2019EA0769, 2021EA0352, 2024EA0523, 2024EA1558,
2023EA0758-A2, 2026EA0391

End of page

SIRIM Berhad
((No. Syarikat 199501038272(367474-V)))

1, Persiaran Dato' Menteri
P.O. Box 7035, Seksyen 2
40700 Shah Alam
Selangor
MALAYSIA.

Tel : 603-5544 6000
Emel : web@sirim.my

Tarikh Mula Pensijilan : 15 April 2016

Certified Since

Sah Sehingga : 15 April 2027

Valid Until

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM Berhad
This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM Berhad

Tarikh Dikeluarkan : 04 August 2026

Issue Date

No Siri : 131280

Serial No